



# MRSP

## restyling pneumatic left side feed

**DESCRIPTION:**

Restyling pneumatic left side feed mini applicator

**CRIMPING HEIGHT:**

135.8mm (5.346")

**STROKE:**

40/30mm (1.575/1.18")

**TERMINAL PITCH:**

> 27mm (>1.06") Max. stroke 35mm

**TERMINAL THICKNESS:**

< 1.2mm (<0.047")

**WIRE SECTION:**

max 10mm<sup>2</sup>

**FEEDING SYSTEM:**

air pressure 5/6 Bar

**WEIGHT:**

4.1 (9.02)

**DIMENSION MM:**

W 140.5 x H 145.5 x D 105

**DIMENSION ("):**

W 5.53" x H 5.72" x D 4.13"

**OPTION:**

Continuous regulating head.  
0.02mm(0.00078") resolution.  
2.7mm(0.106") range



- For linked terminals, with thickness < 1.2mm., terminal pitch > 27mm.
- Pneumatic feeding-system.
- Wire section between 0 and 10mm<sup>2</sup>.
- Feeding system for linked terminals on a reel to be unrolled left to right.
- Can be supplied either with a continuous or a four-pad regulating head.
- Non-resettable 7-digit cycle counter.
- Can be fitted to any crimping press having a crimping height of 135.8mm ± 0.02mm.
- Can be used in both manual and automatic configuration.
- Easy replacement of crimpers and anvils.