

Mecal

BY STARN



www.mecalbystarn.com

MRSP

restyling pneumatic left side feed



- For linked terminals, with thickness < 1.2mm., terminal pitch > 27mm.
- Pneumatic feeding-system.
- Wire section between 0 and 10mm².
- Feeding system for linked terminals on a reel to be unrolled left to right.
- Non-resettable 7-digit cycle counter.
- Can be fitted to any crimping press having a crimping height of 135.8mm (+/-) 0.02mm.
- Can be used in both manual and automatic configuration.
- Easy replacement of crimpers and anvils.
- Bellmouth adjustment can be made without removing from the press

DESCRIPTION:

Restyling pneumatic left side feed mini applicator

CRIMPING HEIGHT:

(5.346") 135.8mm

STROKE:

(1.575/1.18") 40/30mm

TERMINAL PITCH:

> 27mm (>1.06")
Max. stroke 35mm

TERMINAL THICKNESS:

(<0.047") < 1.2mm

WIRE SECTION:

max 10mm²

FEEDING SYSTEM:

air pressure 5/6 Bar -
continuous air (6mm air line)

WEIGHT:

(9.02 lb) 4.1 Kg

DIMENSION (MM):

W 140.5 x H 145.5 x D 105

DIMENSION ("):

W 5.53" x H 5.72" x D 4.13"

CONTINUOUS REGULATING HEAD

(0.00039") 0.01mm resolution.
(0.106") 2.7mm range