

APPLICATORS





- ★ For terminals linked end to end, rolled over a reel, with thickness < 1.2mm, terminal pitch 27-35 mm, wire section between 0 and 10mm2.
- ★ Pneumatic end-feed feeding system.
- Non-resettable 7-digit cycle counter, and with both cams either for terminal feeding.
- ★ Fitted to any crimping press having a crimping height of 135.8mm (+/-) 0.02mm.
- ★ Can be used in both manual and automatic configuration.
- ★ Easy replacement of crimpers and anvils.

MRFP Restyling Pneumatic End Feed

CRIMPING HEIGHT

135.8mm 5.346"

STROKE

40 / 30mm 1.575 / 1.18"

TERMINAL PITCH

< 27mm

< 1.06"

Max stroke 41mm

TERMINAL THICKNESS

< 1.2mm

< 0.047"

Max 25mm²

WIRE SECTION

Max 10mm²

FEEDING SYSTEM

Air Pressure 5/6 Bar

WEIGHT

4.0 Kg

8.8 lb

DIMENSIONS

W 79.5 x H 145.5 x D 157 (mm) W 2.83" x H 5.72" x D 7.73" (inches)

OPTIONS:

CONTINUOUS REGULATING HEAD 0.01mm resolution, 0.00039" 2.7mm range, 0.106"



