

- \star For linked terminals, with thickness < 1.2mm., terminal pitch > 27mm.
- ★ Pneumatic feeding-system.
- \star Wire section between 0 and 10mm².

ECa

FARN

- ★ Feeding system for linked terminals on a reel to be unrolled left to right.
- ★ Non-resettable 7-digit cycle counter.
- ★ Can be fitted to any crimping press having a crimping height of 135.8mm (+/-) 0.02mm.
- \star Can be used in both manual and automatic configuration.
- ★ Easy replacement of crimpers and anvils.
- \star Bellmouth adjustment can be made without removing from the press.





MRSP Restyling Pneumatic Left Side Feed

CRIMPING HEIGHT 135.8mm 5.346″

STROKE 40 / 30mm 1.575 / 1.18"

TERMINAL PITCH < 27mm < 1.06" Max. stroke 35mm

TERMINAL THICKNESS < 1.2mm < 0.047"

WIRE SECTION Max 10mm²

FEEDING SYSTEM Air pressure 5/6 Bar continous air (6mm air line)

WEIGHT 4.1 Kg

9.02 lb

DIMENSIONS W 140.5 x H 145.5 x D 105 (mm) W 5.53" x H 5.72" x D 4.13" (inches)

CONTINUOUS REGULATING HEAD 0.01mm resolution, 0.00039" 2.7mm range, 0.106"